

# THREE PLY FLAT POLYESTER WEB SLING BELT



## FEATURES

- Factor of Safety (Fos) – 6:1
- Working Temperature: 194°F (90°C) or below -40°F (-40°C).
- Lighter than the chain and steel wire rope sling
- Easy to use and high chemical resistance.
- Does not damage the material to be lifted. Positioning is fast and easy.
- Can tighten up the material to avoid slip while lifting the products.
- Only small storage space is required because of its flexibility.
- Medium initial investment cost. However, higher productivity, longer service life, easier handling and storage result in low total operating costs.
- Lightweight and excellent flexibility allow safer and easier handling of your valuable products.
- High resistance to chemical and oil contamination.
- Various sizes available for every application.
- Custom made slings for specific applications can be made to customer specifications.
- Special treatment gives excellent resistance to surface abrasion and cutting.
- Quality is maintained through constant research.

## THREE PLY FLAT POLYESTER WEB SLING BELT

WS03

Item Code(s)	COLOR	WIDTH		CAPACITY IN DIFFERENT SHAPE				THICKNESS
				STRAIGHT	BASKET	CHOKER	0-45	
		Inch	mm	(Ton)	(Ton)	(Ton)	(Ton)	(mm)
WS03-01	VOILET	1	25	1.5	3.0	0.8	1.2	11.25
WS03-02	GREEN	2	50	3.0	6.0	1.6	2.4	11.25
WS03-03	YELLOW	3	75	4.5	9.0	2.4	3.6	11.25
WS03-04	GREY	4	100	6.0	12.0	3.2	4.8	11.25
WS03-05	RED	5	125	7.5	15.0	4.0	6.0	11.25
WS03-06	BROWN	6	150	9.0	18.0	4.8	7.2	11.25
WS03-08	BLUE	8	200	12.0	24.0	6.4	9.6	11.25
WS03-10	ORANGE	10	250	15.0	30.0	8.0	12.0	11.25
WS03-12	ORANGE	12	300	18.0	36.0	9.6	14.4	11.25



## WARNING

Never exceed Working Load Limit

The data of products dimension in the catalogue is just for reference!  
Copyright©2023 | www.jblifting.com | All rights reserved