

Medium

## BESTBOY231 S3

All-time favorite, mid-cut safety shoe

|                 |  |
|-----------------|--|
| Upper           | Barton Action Leather                                |
| Lining          | Mesh   |
| Footbed         | SJ foam footbed                                      |
| Midsole         | Steel  |
| Outsole         | PU/PU  |
| Toecap          | Steel  |
| Safety standard | S3 / SRC   |
| Size range      | EU 36-48 / UK 3.5-13.0<br>US 4.0-13.5 / CM 23.5-31.5 |
| Sample weight   | 0.695 kg   |
| Norms           | EN ISO 20345:2011<br>ASTM F2413:2018                 |



BLK



### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.




### Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



### Self-cleaning outsole

Self-cleaning outsoles are designed to reduce clogging of the profile.



### Oil & fuel resistant

The outsole is resistant against oil and fuel.

**Industries:**

Automotive, Chemical, Cleaning, Construction, Food & beverages, Logistics, Oil & Gas, Industry

**Environments:**

Cold environment, Dry environment, Extreme slippery surfaces, Muddy environment, Uneven surfaces, Warm surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|         | Description  | Measure unit | Result | EN ISO 20345 |
|---------|--|--------------|--------|--------------|
| Upper   | <b>Barton Action Leather</b>                                     |              |        |              |
|         | Upper: permeability to water vapor                               | mg/cm²/h     | 2.2    | ≥ 0.8        |
|         | Upper: water vapor coefficient                                   | mg/cm²       | 25     | ≥ 15         |
| Lining  | <b>Mesh</b>  |              |        |              |
|         | Lining: permeability to water vapor                              | mg/cm²/h     | 49.8   | ≥ 2          |
|         | Lining: water vapor coefficient                                  | mg/cm²       | 398.8  | ≥ 20         |
| Footbed | <b>SJ foam footbed</b>   |              |        |              |
|         | Footbed: abrasion resistance                                     | cycles       | 400    | ≥ 400        |
| Outsole | <b>PU/PU</b>   |              |        |              |
|         | Outsole abrasion resistance (volume loss)                        | mm³          | 56.4   | ≤ 150        |
|         | Outsole slip resistance SRA: heel                                | friction     | 0.37   | ≥ 0.28       |
|         | Outsole slip resistance SRA: flat                                | friction     | 0.34   | ≥ 0.32       |
|         | Outsole slip resistance SRB: heel                                | friction     | 0.14   | ≥ 0.13       |
|         | Outsole slip resistance SRB: flat                                | friction     | 0.18   | ≥ 0.18       |
|         | Antistatic value   | MegaOhm      | 120.7  | 0.1 - 1000   |
|         | ESD value  | MegaOhm      | N/A    | 0.1 - 100    |
|         | Heel energy absorption   | J            | 29     | ≥ 20         |
| Toecap  | <b>Steel</b>   |              |        |              |
|         | Impact resistance toecap (clearance after impact 100J)           | mm           | N/A    | NA           |
|         | Compression resistance toecap (clearance after compression 10kN) | mm           | N/A    | NA           |
|         | Impact resistance toecap (clearance after impact 200J)           | mm           | 15     | ≥ 14         |
|         | Compression resistance toecap (clearance after compression 15kN) | mm           | 15     | ≥ 14         |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com